



Aumüller Druck Regensburg

Creating a Printing PDF for Aumüller Druck – a Short Guide

We ask you to send us

- Standard composite PDF, for example PDF X-4. Pages arranged as single pages and also including blank pages. PDF exported from Adobe InDesign (Version 3.0 and higher). We recommend to use our job options (see below).
- Please contain the page numbers in the file name, e. g. „smith_001-030.pdf“. Please use short file names without special characters or blanks.
- Please provide every part of the product as a separate file, e. g. cover, text or chapters.
- Please add 10 mm (0,4 inches) extra space to the finished / trimmed size on every margin. E. g. the finished size of 210 x 297 mm needs a file size of 230 x 317 mm.
- Please add 3 mm (0,12 inches) bleed if necessary.
- Trim marks should be at least 3 mm (0,12 inches) kept away from the finished size.
- File resolution: 2400 to 2540 dpi, screen ruling: 175 lpi.
- Images: Colour space CMYK. Resolution at least 200 dpi in printing size. Resolution for line art at least 1200 dpi.
- Line weight at least 0,1 mm (0,004 inches).
- All fonts embedded.
- All colours defined as CMYK. Except spot colours.
- Please make sure to use the right settings for overprint and knock-out. If there is any special issue, please contact our sales person or one of our prepress operators.
- Please provide a colour consistent contract proof of pictures and/or illustrations. The proof must contain a Ugra/Fogra Media Wedge CMYK V3.0

Exceptions / Special Issues

- For multiple versions or languages, please contact us for further information.

Further recommendations

- Adobe Acrobat Distiller job options for Mac OS-9, OS-X or Windows see: www.aumueller-druck.de/Downloads
- For ICC colour profiles see <http://www.eci.org/en/downloads>.
- For Informations on the PDF X standard see <http://www.gwg.org/gwg-2012-specifications/>.